

Sucker Rod String: Polished

PDS: SRPRSMWF

Short Name: Q08


Effective Date: 9/18/2024
Previous Revision: 10/13/2017

Spray Metal Polished Rod with Wrench Flats

Product Description:

Polished Rods can be manufactured with two or four wrench flats depending on client's needs.

Dimensions:



Nominal Size		Units	Dpr	L3s	Lpf	Lwf	Wwf
Rod	Pin	Ullits	υμι	LJS	(min)	(min)	VVVVI
			1.125				1.000
		in	+0.005	1.406	0.197	1.250	+0.031
1 1/4"	7/8'' PR		-0.010				-0.031
11/4	770 110		28.6	35.7	5.0	31.8	25.4
		mm	+0.1				+0.8
			-0.2				-0.8
	1" PR		1.500				1.311
1 1/2"		in	in +0.005 1.78 0.197 1.500	1.500	+0.031		
			-0.010				-0.031
		mm	38.1	45.21	5.0	38.1	33.3
			+0.1				+0.8
			-0.2				-0.8
1 1/2"		in	1.500	-	0.197	1.500	1.311
			+0.005				+0.031
	1" PR - 3/4" PR		-0.010				-0.031
	1 110 3/4 110		38.1				33.3
		mm	+0.1	-	5.0	38.1	+0.8
			-0.2				-0.8

Available Lengths* (Lpr): 8, 11, 16, 22, 26, 30, 36 ft ± 2"

(2.438, 3.353, 4.877, 6.706, 7.925, 9.144, 10.973 m ± 50.8 mm)

Steel Grades:

Chemical Composition:

Typical chemical compositions (wt%) are listed in the following table.

Grade	С	Mn	Si	S	Р	Cr	Ni	Мо	Others
Carbon steel	0.43-0.50	0.60-0.90	-	0.050 max	0.040 max	-	-	-	-
Alloy steel	0.38-0.45	0.75-1.00	0.15-0.35	0.040 max	0.040 max	0.80-1.10	-	0.15-0.25	-

^{*}Other lengths might be available upon request.

Mechanical Properties:

Mechanical properties are listed in the following table.

Grade	Ultimate Tensile Stress				
Carbon steel	90 to 160 kpsi				
Carbon steer	(620 to 1102 MPa)				
Alloystool	115 to 140 kpsi				
Alloy steel	(793 to 964 MPa)				

Coating:


Spray Metal Chemical composition in accordance with API 11B

Roughness (Ra): 8-20 μin (0.203-0.508 μm) **Min thickness:** 0.008-0.02 in (0.2-0.51 mm)

Hardness: 480 HV200 min
Coating length: Full length

Coating	С	SI	P	S	Cr	В	Fe	Ni	Others
Spray Metal	0.50 - 1.00	3.50 - 5.50	0.02 max	0.02 max	12.00- 18.00	2.50 - 4.50	3.00 - 5.50	Remainder	Ti: 0.05 max Al: 0.05 max Zr:0.05 max Co:0.10 max

Marking:



Metalmecánica S.A. Tenaris 🗮 Ruta 55 Km. 754,1 Villa Mercedes (San Luis) Made in Argentina BOX N° QTY: 60000005 PRODUCT: POLISHED ROD DATE: SPECIFICATION: ROD DIAM (in): GRADE LENGTH: NET WEIGHT: (kg) SALES ORDER DESTINATION:

*Image for reference only

Non Destructive Testing:

All raw material is carefully inspected using electromagnetic and/or ultrasonic methods to ensure the soundness of the final product.

Ordering Information:

When placing an order please attach the following information:

PDS: SRPRSMWF
Body diameter: 1 1/2"
Pin diameter: 1" PR

Surface finish: Spray Metal Grade: Carbon steel

Length: 30 ft Wrench flats: 2

Tenaris has issued this document for general information only, and the information in this document is not intended to constitute professional or any other type of advice or recommendation and is provided on an "as is" basis. No warranty is given. Tenaris has not independently verified any information –if any– provided by the user in connection with, or for the purpose of, the information contained hereunder. The use of the information is at user's own risk and Tenaris does not assume any responsibility or liability of any kind for any loss, damage or injury resulting from, or in connection with any information contained hereunder or any use thereof. The information in this document is subject to change or modification without notice. Tenaris's products and services are subject to Tenaris's standard terms and conditions or otherwise to the terms resulting from the respective contracts of sale or services, as the case may be. Unless specifically agreed under such contract of sale or services, if Tenaris is required to provide any warranty or assume any liability in connection with the information contained here under, any such warranty or liability shall be subject to the execution of a separate written agreement between petitioner and Tenaris. For more complete information please contact a Tenaris's representative or visit our website at www.tenaris.com. All rights reserved. ©Tenaris 2024